

Gradall® Telehandlers

Discover the Rear-Pivot Steering Advantage



JLG® The Power To Do More

GRADALL®

90° REAR-PIVOT STEERING ▶

Gradall® telehandlers can maneuver and turn sharply on an axis allowing the operator to move, square and place loads with precision.

Nothing Maneuvers

Gradall® Advantages

Maneuverability & Precision Handling

- 90° rear-pivot steering for negotiating narrow aisles or crowded job sites.
- Mid-mounted engine provides balanced weight distribution, allowing operation in mud, rocks or sand.
- Long wheelbase for low center of gravity and stability on rough terrain.
- No-shift hydrostatic drive train provides the precision handling operators need to inch the machine into exact positions for critical load placements.

Versatility & Efficiency

- Quick-Switch attachments turn your base machine into a versatile productivity tool for dozens of job site challenges.
- Spacious and comfortable operator cab provides protection and a clear view.
- Convenient single joystick control for boom lift and crowd.

Strength & Reliability

- Higher capacities throughout lift range.
- Rugged design and proven durability for lower cost of operation.





Like a Gradall® Telehandler

What Can You Do with a Gradall Telehandler?

Gradall telehandlers are widely recognized for their strength, reliability and low cost of ownership. But it's their exclusive 90° rear-pivot steering that sets them apart. And gives you outstanding maneuverability even in the tightest work areas. Operators can take them where other telehandlers can't go. They can turn sharp corners, move down narrow aisles and square-up lumber and block in crowded landing areas with greater speed and accuracy. All with a clear view of the job site from the comfort of a spacious machine cab. Plus, Gradall telehandlers can be equipped with a full range of attachments to handle a wide variety of jobs. For the high level performance you need, there's almost nothing a Gradall Telehandler can't do.



Makes sharp turns around corners and obstacles. Turns within its outside radius for narrow or enclosed areas.




Gradall Telehandlers

Backed by the Power of JLG

Gradall telehandlers are backed by the strength and technology of JLG, with the most powerful service, parts, support and distribution in the world. You'll have everything you need to keep your machine on the job, whenever and wherever you need it.

Attachments to help you get the job done

Choose from a wide variety of Quick-Switch attachments and turn your Gradall telehandler into a versatile productivity tool capable of handling dozens of job site challenges. Our exclusive boom-end designs allow a single operator to change from one attachment to another in seconds.

Model	Rated Capacity	Maximum Lift Height	Capacity @ Max. Lift Height	Maximum Reach	Capacity @ Max. Reach	Engine
 Gradall G6-42P	6,600 lb (2,994 kg)	42 ft (12.8 m)	6,000 lb (2,722 kg)	29 ft (8.84 m)	1,300 lb (590 kg)	John Deere 4045DF150
 Gradall 534D9-45	9,000 lb (4,082 kg)	45 ft (13.7 m)	7,000 lb (3,175 kg)	31 ft 6 in. (9.6 m)	1,600 lb (726 kg)	John Deere 4045TF275
 Gradall 534D10-45	10,000 lb (4,536 kg)	45 ft (13.7 m)	7,000 lb (3,175 kg)	31 ft 6 in. (9.6 m)	4,500 lb* (2,041 kg)	John Deere 4045TF275
 Gradall 544D10-55	10,000 lb (4,536 kg)	55 ft (16.76 m)	5,000 lb* (2,268 kg)	42 ft (12.8 m)	3,000 lb* (1,361 kg)	John Deere 4045HF275

PLEASE NOTE: These limited specifications are for reference only. Please refer to appropriate specification sheet for complete information.
*Stabilizers are required to achieve stated capacity.

Quick-Switch Attachments



Truss Boom

Place roof trusses with precision and lower materials into tight spots.



Light Material Handling Bucket

Clean up the job site or spread gravel or rip-rap with a range of buckets.



Personnel Work Platform

Place people and materials where they're needed for optimum productivity.



Side-Tilt Carriage

Maintain a level load even on hillsides and rough terrain.



Winch

Deliver loads behind walls or from behind tall obstructions with an instant hook that is securely and permanently fixed to the boom end.



Swing Mast

The swing mast increases lift height by six feet and then swings 50 degrees either right or left.



Swing Carriage

Extend the boom and swing the carriage right or left by 50 or 90 degrees.



Drywall Carriage

Avoid drywall damage and speed up unloading and placement through doors and windows.



Pallet Forks

Choose from a wide range of forks of varying thicknesses, widths and lengths.



Cubing Forks

Load, unload and place cubes of brick and block with ease.



Clear Path Material Bucket

The 102-inch (259 cm) wide bucket cleans aisles and access paths with one pass.



Broom Sweeper

Ideal for brushing debris from job site pathways, brushing away snow or handling light cleanup.



The Power To Do More

JLG Industries, Inc.
1 JLG Drive, McConnellsburg, PA 17233-9533
Telephone 717-485-5161
Toll-free in US 877-JLG-LIFT
Fax 717-485-6417
www.jlg.com

Form No.: B-GRAD-0205-15M
Part No.: 3132215
Printed in USA

